

# **IT-S15**

### Professional Active Performance System

#### **DESCRIPTION**

IT-S15 is an active two-way 9-unit inverting full-range speaker, specially designed for small touring performance.

IT-S15 is a perfect sound reinforcement solution that can be used quickly and easy setup . Installment and interconnecting can be done with one minute, easily carry with bags. No need extra power amplifier, mixer or any other speakers, one set Meline S15 with MP3, bluetooth and connecting with laptop , you get everything.

It is a high-power, high SPL wooden speaker with one 15" woofer and 8  $\times$  2" full-frequency units and Bi-amp module of CLASS D. Adjustable angle support rod, you can enjoy the most realistic and beautiful sound though it whatever you stand or sit.



## **FEATURES**

- Compact, small and high SPL
- Specially designed for small touring performance -

Portable and easy installation design

- Max.SPL 132dB (peak)
- Bi-amp module of CLASS D -

Bluetooth connection available



#### **TECHNICAL SPECIFICATIONS**

$\begin{tabular}{ll} Max SPL @ 1m: & 119dB/132dB (Peak) \\ \hline Dispersion (H x V): & 100° x 40° \\ \hline Transducers & 8 x 2" Full-frequency unit \\ \hline Woofer: & 1x 15" Woofer \\ \hline Input/Output section & Input Connectors: & Three channel balanced input XLR/ 6.35[]TRS[]RCA \\ \hline Power section & 550W(RMS): 1100W(MUSIC): 2200W(PEAK): \\ \hline Mid frequencies: & 200W \\ \hline Low frequencies: & 350W \\ \hline Nominal Impedance (Ohm): & 4\Omega \\ \hline Cooling: & Forced air-cooled drives \\ \hline \end{tabular}$	
Transducers       Compression driver: $8 \times 2^{"}$ Full-frequency unit         Woofer: $1 \times 15^{"}$ Woofer         Input/Output section       Input Connectors:       Three channel balanced input XLR/ 6.35[TRS[]RCA         Power section       Total Power: $550W$ (RMS); $1100W$ (MUSIC); $2200W$ (PEAK);         Mid frequencies: $200W$ Low frequencies: $350W$ Nominal Impedance (Ohm): $4Ω$	
Woofer: $1 \times 15^{"}$ Woofer       Input/Output section     Input Connectors:     Three channel balanced input XLR/ 6.35[TRS[RCA       Power section     Total Power: $550W(RMS)$ ; $1100W(MUSIC)$ ; $2200W(PEAK)$ ;       Mid frequencies: $200W$ Low frequencies: $350W$ Nominal Impedance (Ohm): $4\Omega$	
Input/Output section   Input Connectors: Three channel balanced input XLR/ 6.35 [TRS [RCA   Fower section   Total Power: $550W(RMS)$ ; $1100W(MUSIC)$ ; $2200W(PEAK)$ ;   Mid frequencies: $200W$   Low frequencies: $350W$   Nominal Impedance (Ohm): $4\Omega$	
Power section         Total Power:         550W(RMS); 1100W(MUSIC); 2200W(PEAK);           Mid frequencies:         200W           Low frequencies:         350W           Nominal Impedance (Ohm):         4Ω	
$\begin{tabular}{lllllllllllllllllllllllllllllllllll$	
Low frequencies: 350W   Nominal Impedance (Ohm): $4\Omega$	
Nominal Impedance (Ohm): 4Ω	
Cooling: Forced air-cooled drives	
Power consumption(static): 28W	
Power consumption(rated): 400W	
Voltage range: AC 110V/230V, 50Hz/60Hz	
Physical specifications Cabinet/Case Material: Plywood,column loudspeaker	
Handles: 2 x Wooden handles + 1 x Aluminum handle	
Cabinet coated by Polyurethane paint; grille is powder coated	inside is black
Grille: cotton	
Color: Black	
Size Dimension (W x D x H): 420 x 490 x 2021mm / (16.5 x 19.3 x 79.6in)	
Package Dimensions (W x D x H): 720 x 515 x 655mm / (28.3 x 20.3 x 25.8in)	
Weight Net Weight: 27.3 kg / 60.2 lb	
Gross Weight: 32.55 kg / 71.8 lb	

Note: Images are illustratative purpose only and specification are subject to changes without prior notice for the enhancement of product quality.