

## TS-0223

## Full Digital Conference Embedded Delegate Unit

## TS-0223A



TS-0223



TS-0223A

### Feature

\*With full digital induction touch embedded design, delicate appearance, the touch panel with compact design, easy to operate, full of modern sense of science and technology.

\*Using the new CNC design, capacitive touch buttons, no mechanical noise, buttons with long life, waterproof design.

\*The microphone adopts 48KHZ sampling rate, higher than the CD sound quality, the voice is clear and bright. Built-in DSP audio processing, there is no low frequency sound.

\*Support speech timer and timing speech function.

\*Delegate unit apply for speech function, the chairman unit can approve the applicant.

\*Chairman unit has the priority function, which can turn off all delegate units during speaking.

\*With the feedback inhibition function, can effectively prevent the noise.

\*Microphone has voice-control model to open the microphone smartly.

\*5 Section EQ regulating function, different sound effects can be adjusted according to the characteristics of the speaker's voice, to achieve perfect effect.

\*Adopt 100m network transmission to realize hand-in-hand cascading, long-distance transmission will not influence the sound quality.

Model	TS-0223/ TS-0223A
Microphone Type	Heart shaped directivity electrets
Frequency Response	80Hz-16KHz
Microphone Input Impedance	1KΩ
Sensitivity	-46dBV/Pa
SPL Max SPL	125dB (THD>3%)
Noise-Signal Ratio	>80dB (A)
Dynamic Range	>80dB
THD	<0.1%
Power Dissipation	1.8W
Follow Specification	IEC60914
Connector	With 1.8 meters of aviation core 6
Power Supply Mode	Host power supply
Color	Grey
Sign In Function	Sign in by touch keys
Weight	0.5Kg
Microphone Stem Height	415mm
Installation Mode	Embedded
Table Hole Size	65x54mm
Dimension(LxWxD)	108x77x129mm