

TECHNICAL SPECIFICATION

Specification	IS-150
Speaker Type	Main Speaker
Number of Speaker	2
Continuous Program Power Capacity	50 Watt.
Sensitivity	86db SPL, 1w, 1m
Directivity Factor (Q)	4.8
Directivity Index (DI)	6.8
Nominal Impedance	6ohms
Termination	Spring Terminals, accepts banana plugs
Crossover Frequency	3.5 kHz
LF Driver	88 mm (3.5in) Polypropylene cone w/Weather Edge
Frequency Range (-10 db)	85 Hz to 22 kHz
Power Rating	50 watts
Environmental	Conforms to Mil Spec 810 for humidity, Salt Spray temperature & UV. IEC 529 IP-X4 Splashproof Rating
Enclosure	Textured Black H.I.P.S. Plastic
Mounting	Wall
Dimensions (H x W x D) (mm x mm x mm)	406 mm x 343 mm x 224 mm
Weight (Kg)	1.8
AC Power Input	230V ~ 50/60 Hz

Remarks:

- **THE ABOVE SPECIFICATIONS CAN BE CHANGED WITHOUT PRIOR INFORMATION.**
- **THE IMAGES SHOWN FOR ILLUSTRATION PURPOSE ONLY. ACTUAL PRODUCT MAY VARY DUE TO PRODUCT ENHANCEMENT.**