

IT-PS24

Intellitech IT-PS24 chassis based Production Switcher allows you to bring multiple video sources and switch between them while you are recording or live streaming. These sources include camera feeds, presentation slides, remote guests, pre-recorded video sources or shared screens. You can normally add transition effects to make it appear even more professional. To add additional production value for your multi-camera production, you can utilize video mixers' builtin graphic capabilities or leveraging external graphics generators to add



Logos, image overlays, lower-thirds, scoreboards, rolling texts, motion graphics and comment overlays to make the video or live stream more informative and engaging. Utilizing multiple video sources also allows for the creation of varied multiviews such as Picture in Picture, Side-By-Side, and Split Views to add depth and richness of your content and storytelling.



IT-PS24

Features:

- 2.2 inch LCD, 24 LED buttons for switching, 10 source buttons four transition buttons. Six talkback selection and mix buttons. Menu control knob and set button lock button
- Featured with Tri-Sync or Black Burst
- Control using Controller via Ethernet Port



Specifications:

Model	IT-PS24
Inputs	24 x 3G-SDI
Outputs	24 x 3G-SDI
Audio Inputs	2 x 6.3 Jack, 1 x XLR
Audio Outputs	1 x XLR
USB	USB-C to connect any peripheral device such as Camera
HD Video Standards	720p50, 720p59.94, 720p60 1080i50, 1080!59 94, 1080i60 1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p50, 1080p59.94, 1080p60
SDI Compliance	SMPTE 292M, SMPTE 296M SMPTE 424M, SMPTE 425M level A and B
Layers	14

*Picture for illustration purpose only



IT-PS24

Pattern	10
Color Generators	3
Control	Software and Hardware
Multi View Monitoring	2 x multi views each configurable to 16, 13, 10, 7, 4
Super Source	2
Video Sampling	4:2:2 at 10-bit Color Precision
Upstream Keyers	8
Downstream Keyers	2
Advanced Chroma Keyers	6
Linear/Luma Keyers	10
Transition Keyer	4 stinger, 4 DVE
(Stinger/DVE)	
Display Resolution	1920 x 1080
Media Players	4
Media Pool Still Image	40
Capacity	
Media Pool Clip Capacity	2 (1080p60)
Media Player Clip Length in	800 Frames
720 HD	
Media Player Clip Length in	400 Frames
1080 HD	
Media Pool Still Image	BMP, GIF, PNG, TGA, JPEG and TIFF
Format	
Media Pool Audio File	AIFF, MP3 and WAV
Format	
Controller	
LAN	2 x 1G Ports
USB	USB-C
Button Type	Tri-Color LED
Macro Buttons	12
Fader	1
Preview	1
Menu Display	3
Control Buttons	24
Joystick	1
Numeric Keypad	1
Display	Matrix Display
On-Air	6
DSK Transition Selectors	Auto, Cut, Tie/Preview

PRODUCTION SWITCHER



IT-PS24

Shifted Cross Points	20
Direct Cross Points	10

*Picture for illustration purpose only