

IT-LIVE12 CAMERA SWITCHER



[Product Overview](#)

The IT-LIVE12 is a professional video production switcher with a 15.6-inch touch display. Compared with traditional production switchers, the IT-LIVE12's larger display provides a clearer interface and allows you to view more operation menus and video content simultaneously. Whether you are switching camera feeds, adjusting parameters, or monitoring multiple outputs, the operation is straightforward, efficient, and intuitive. The IT-LIVE12 is equipped with four 12G-SDI inputs and four HDMI 2.0 inputs, providing a total of eight input channels.

From 4K cameras to high-resolution computer sources, the IT-LIVE12 seamlessly integrates into your production environment and ensures broadcast-grade image quality.

[Key Features](#)

- 15.6-inch touchscreen for intuitive control and real-time monitoring.
- 4K UHD input for high-resolution multi-camera production.
- 4K loop output for 4K display systems.
- Audio faders for smooth audio level adjustment.
- Dual USB interfaces supporting simultaneous recording and UVC camera input.
- Integrated media player for video playback.
- PGM and MV outputs enabling flexible program and preview monitoring.
- Portrait and landscape production scenarios.
- Built-in web control interface accessible via standard web browsers.
- Dual-channel live streaming over Ethernet with configurable stream keys.
- Supports Dual USB Ports USB Recording and USB Feed Simultaneously
- Supports Flexible PGM & MV Output
- Supports Landscape & Portrait Layout Within the Screen for Various Scenarios
- Dual Channel RTMP Streaming Through Ethernet
- Built-in Media Player for Direct Playback
- Supports Recording by USB Disk and HDD
- Built-in Web Server, Supporting Web Browser Control Across All Platforms

SPECIFICATIONS:

Input	4x12G SDI SDI 1080p Input 4xHDMI HDMI 4k Input 1xUSB USB-A Video Playback/image Loading/uvc Input
Output	2x12G SDI PGM Output 1xHDMI-A PGM Output 1xDP MultiView 1xUSB A UVC Output
Audio	2x6.35mm Input 1x3.5mm Output
Control	1xRJ45 Network Control PTZ Camera Control
Input Resolution	3840x2160p60/59.94/50/30/29.97/25 1080p60/59.94/50/30/29.97/25 1080i60/50
Output Resolution	3840x2160p60/59.94/50/30/29.97/25
Performance	Video Sampling YUV 4:4:4
Power	12V/3A 30W
Operating Environment	Operating Temperature 0°C~70°C Operating Humidity 10%~85%