

IT-LIVE5 CAMERA SWITCHER AND RECORDER



[Product Overview](#)

The IT-LIVE5 is a professional video production switcher with a 10.1-inch touch display. Compared with traditional production switchers, the IT-LIVE5's larger display provides a clearer interface and allows you to view more operation menus and video content simultaneously. Whether you are switching camera feeds, adjusting parameters, or monitoring multiple outputs, the operation is straightforward, efficient, and intuitive. The IT-LIVE5 is equipped with four 3G-SDI inputs and four HDMI 2.0 inputs, providing a total of eight input channels.

It supports two HDMI outputs, one fixed HDMI loop-through output, and one SDI output, meeting the needs of diverse live production scenarios.

From 4K cameras to high-resolution computer sources, the IT-LIVE5 seamlessly integrates into your production environment and ensures broadcast-grade image quality.

For audio control, the IT-LIVE5 supports two XLR audio inputs and three independent faders, enabling smooth volume adjustment and professional-grade mixing.

[Key Features](#)

- 10.1-inch touchscreen for intuitive control and real-time monitoring.
- 4K UHD input for high-resolution multi-camera production.
- 4K loop output for 4K display systems.
- 3.5 mm and XLR audio inputs for professional audio equipment.
- Three audio faders for smooth audio level adjustment.
- Dual USB interfaces supporting simultaneous recording and UVC camera input.
- Integrated media player for video playback.
- PGM and MV outputs enabling flexible program and preview monitoring.
- Internal recording to USB drives or external hard disks.
- Portrait and landscape production scenarios.
- Built-in web control interface accessible via standard web browsers.
- Dual-channel live streaming over Ethernet with configurable stream keys.
- Supports Dual USB Ports USB Recording and USB Feed Simultaneously
- Supports Flexible PGM & MV Output
- Supports Landscape & Portrait Layout Within the Screen for Various Scenarios
- Dual Channel RTMP Streaming Through Ethernet
- Built-in Media Player for Direct Playback
- Supports Recording by USB Disk and HDD
- Built-in Web Server, Supporting Web Browser Control Across All Platforms
- Dual-Channel XLR Audio Interface

SPECIFICATIONS:

Input	4xSDI SDI 1080p Input 4xHDMI HDMI 4k Input 2xUSB USB-A Video Playback/image Loading/unc Input
Output	1xSDI PGM Output 1xHDMI-A PGM Output 1xHDMI-A PVW / PGM / PST Selectable Output 1xUSB Type-C UVC Output
Audio	2x3.5mm Audio Jacks Compatible With Mic/line Stereo Input 2x6.35mm XLR Jacks Compatible With Mic/line Stereo Input 1x3.5mm Audio Jack Monitoring Output 1x3.5mm Audio Jack Linear Output
Control	1xRJ45 Network Control PTZ Camera Control
Input Resolution	720p50/60、1080i50/60、1080p24/30/50/60 720p50、720p59.94、720p60、1080p23.98、1080p24、1080p25 1080p29.97、1080p30、1080p50、1080p59.94、1080p60、1080i50 1080i59.94、1080i60、2160p30/50/60
Output Resolution	1080p24/25/30/48/50/60
Performance	Video Sampling YUV 4:4:4
Power	12V/3A 30W
Operating Environment	Operating Temperature 0°C~70°C Operating Humidity 10%~85%