



IT-CSXP SERIES

Features:

- Coaxial full range ceiling loudspeaker
- Powder coated perforated steel grille with dust protection and Zinc plated steel back can
- With line transformer and 70V/100V tapping switch
- Four Pole Phoenix connector (Loop-Through wiring)

*Picture for illustration purpose only



Specifications:

Model	IT-CS4P	IT-CS5P	IT-CS6P
Driver	4"×1 1"×1	5"×1 1.5"×1	6.5"×1 1.5"×1
Power	40W RMS, 160W PEAK	60W RMS, 120W PEAK	60W RMS, 200W PEAK
Rated power (100V)	1.75W, 3.75W, 7.5W	3.75W, 7.5W, 15W, 30W	3.75W, 7.5W, 15W, 30W
Rated power (70V)	1.9W, 3.75W, 7.5W, 15W, 30W	1.9W, 3.75W, 7.5W, 15W, 30W	1.9W, 3.75W, 7.5W, 15W, 30W
Frequency Response	20Hz-20kHz		
Dispersion (H x V)	160°		
Max SPL @ 1m	108dB		
Sensitivity (1W @ 1m)	90dB		
Nominal Impedance (Ohm)	8 Ω		
Grille	Steel powder coating		
Working Temperature	0 – 50°C		
Humidity	10 – 90% RH, Non-condensing		

*Picture for illustration purpose only