

**Features:**

- Designed for professional sound reinforcement, conferencing, public address, and commercial audio applications.
- Features interchangeable condenser microphone capsules that deliver natural, full-range, and high-fidelity audio reproduction.
- Supports multiple interchangeable microphone elements with selectable pickup patterns, offering coverage angles from 90° to 360° to suit different installation requirements.
- Equipped with a slim, flexible gooseneck that enables precise microphone positioning while maintaining an elegant appearance.
- Incorporates advanced RF shielding technology to effectively suppress radio frequency interference (RFI) from mobile phones, wireless devices, and other electronic equipment.
- Available in multiple gooseneck lengths to accommodate various podium, lectern, desktop, and installation applications.
- Engineered to deliver clear, consistent, and reliable voice reproduction in demanding professional environments.

*Picture for illustration purpose only



- Rugged construction ensures long-term durability and dependable performance for continuous commercial use.
- Suitable for conference rooms, auditoriums, lecture halls, houses of worship, government facilities, educational institutions, and corporate boardrooms.

Specifications:

Model	IGMU
Type	Fixed-charge back plate, condenser Microphone
Frequency Response	20-20,000 Hz
Dynamic Range	118 dB
Signal-to-Noise Ratio	72 dB
Maximum SPL	145 dB SPL
Sensitivity	-34 dB (18.0 mV) re 1V at 1 Pa
Phantom Power	11-52V DC
Switches	Toggle on/off; LED Color: mic Mute, mic Unmute; Switch function: touch on/off, Touch to Mute, Touch to Talk
Connector	XLR
Optional Interchangeable Elements	Cardioid, Hyper cardioid, Omnidirectional
Gooseneck Length	6", 12", 15", 18", 21", 24"

*Picture for illustration purpose only