# Intellitech TX/RX

## HDMI HDBaseT Extender

## U-HDBR-HD-330TR-AR




* Picture for illustration purpose only

https://www.intellitechglobal.com

## Specification

| | | |
|---|---|---|
| **Input** | 1*HDMI，1*3.5MM Audio, 1*RS232, 1*IR-TX, 1*IR-RX | 1*HDBaseT |
| **USB** | USB supported | 1*USB 2.0/3.0 |
| **Output** | 1*HDBaseT | 1*HDMI，1*3.5MM Audio, 1*RS232, 1*IR-TX, 1*IR-RX, USD HID |
| **Protocol** | Support HDMI1.4a and compatible with HDCP, EDID Management | |
| **Resolution** | 480i, 576i, 480p, 576p, 720p, 1080i, 1920 x 1080p up to 60Hz 3840/4096 x 2160 up to 30Hz | |
| **Color Space** | 1080p: 36Bit Deep Color 4K: 24Bit True Color, 4:2:2 | |
| **Bandwidth** | 10Gbps | |
| **Transmission Distance** | CAT5e/6 cable: 330FT (1080p60Hz)<br>220FT (4K30Hz) | |
| **Dimension** | 152*100*27(mm) | |
| **Weight** | 200g | |
| **Power** | AC: 100-240V 50/60Hz 1.5A Max DC: 12V 1500mA | |
| **Consumption** | ≤11W | |
| **Working Humidity** | 10%-90% | |
| **Working Temperature** | 0℃-50℃ | |
| **Storage Temperature** | -20℃-75℃ | |

* Picture for illustration purpose only