



The INTELLITECH IT-WGM-400 is a range of high quality UHF wireless microphone systems; deliver uncompromised high quality sound reproduction that professional demand.

Features:

Metal chassis equipped with a LCD screen and electronic buttons on the front panel. The LCD screen will automatically turn bright to identify "Working" or "Standby" mode. Pilot Tone & Noise Lock circuits and the RF interference-warning indicator for proper adjustments of the SQ level to avoid interference. Each channel has separate audio output and mix signals from all channels with just one output jack. All is to ensure the microphone operates within proper sensitivity and dynamic range, free from distortion. Long battery life and multiple microphone attachments- Handheld, Lapel, Headworn.



*Picture for illustration purpose only



Specifications:

| | |
|---------------------------|-------------------------|
| Frequency Range | 470-1930 MHz |
| Frequency Response | 20-20KHz |
| Transducer type | Dynamic |
| Polar pattern | Cardioid/supercardioid |
| Total Harmonic Distortion | ≤-60dB |
| Audio Output Level | 24 dBu |
| Latency | 1.5 ms |
| Max. SPL | 162 dB |
| Dynamic range | 142 dB |
| sensitivity | 19mV/Pa |
| Voltage range | AC 100V/240V, 50Hz/60Hz |
| Battery voltage | 1.5v |

*Picture for illustration purpose only